



Ip of surface video intercom

VTO3211D-P2-S1

CAMERA

Resolution	2 Mpx
Sensor	CMOS
Sensor size	1/2.8"
Focal distance	1.9mm
Horizontal viewing angle	134°
Diagonal angle of view	151°
Day / Night	Mechanical
Video compression	H.264

POWER CONSUMPTION

Power mode	DC
Voltage	12V
Consumption (w)	6W
Amperage	500mA
PoE power	Yes
Type PoE	PoE 802.3af

INPUTS/OUTPUTS

Alarm input	2
RS485	1
Door sensor	1
Alarm output	1

SPECS AND FEATURES

Technology	IP
Number of homes	2

OPENING

Call elements	2 Botones sencillos
Proximity reader	MIFARE cards

GENERAL CHARACTERISTICS (VIDEO INTERCOM)

Tamper	Sí
--------	-----------

AMBIENT

Operating temperature	-30 °C ~ 60 °C
Degree of protection	IP65
Anti vandal	IK08
Use	Outdoor
Maximum humidity	90%

MATERIAL AND DIMENSIONS

Installation	Surface
Dimensions	182 x 30 x 101 mm
Material	Aleación de zinc
Net weight	800 g

AUDIO (VIDEO INTERCOM)

Sound input	Multidirectional microphone
Sound output	Built-in speaker
Bidirectional audio	Sí
Audio compression	G.711

SYSTEM (RECORDERS)

Processor	Embedded Micro Processor
Operating system	Embedded LINUX

NETWORK CHARACTERISTICS (INTERCOM MONITORS)

Network protocol	TCP / IP
IP connection	10 / 100Mbps autoadaptive