technical datasheet



NINX

Wireless panel HUB-W

ADDITIONAL FEATURES

Software Update	Sí
Mobile app	Ajax Security System
SMS notification	Sí
Call notification	Sí
Notificación Push	Sí
Maximum number of connected IP cameras	10
Mobile devices	iOS 9.1 or later / Android 4.1 or later

POWER CONSUMPTION

Voltage	110V ~ 250V
Battery life	± 14 hours
Battery support	Li-ion 2 A/h

VIA RADIO

Frequency	868mHz
Transmission distance	Up to 2000 meters
Maximum power RF	Potencia maxima RF

ZONES

Maximum number of rooms	50
Maximum number of devices	100

SABOTAGE

Box tamper	Sí
Wall tamper	Sí

SPECS AND FEATURES

Type of Central	Wireless
-----------------	----------

MATERIAL AND DIMENSIONS

Dimensions	163 x 163 x 36 mm
Net weight	330 g
Color	White
COMMUNICATION	
IP	Sí
GPRS	Sí
Communication with CRA	Sí
AMBIENT	
Operating temperature	-10 °C ~ 40 °C
Use	Indoor
CERTIFICATION	
Grade	2
Normative	EN50131
PROCCESSOR	
Processor	ARM
Operating system	OS Malevich



50

PARTITIONS AND MEMORIES