technical datasheet



NINX

Wireless panel HUB-W

ADDITIONAL FEATURES

Software Update	Sí
Mobile app	Ajax Security System
SMS notification	Sí
Call notification	Sí
Notificación Push	Sí
Maximum number of connected IP cameras	10
Mobile devices	iOS 9.1 or later / Android 4.1 or later

POWER CONSUMPTION

Voltage	110V ~ 250V
Battery support	Li-ion 2 A/h
Battery life	± 14 hours

VIA RADIO

Frequency	868mHz
Transmission distance	Up to 2000 meters
Maximum power RF	Potencia maxima RF

CERTIFICATION

Grade	2
Normative	EN50131
SABOTAGE	

SABOTAGE

Box tamper	Sí
Wall tamper	Sí

GENERAL INFORMATION

Type of Central	Wireless
-----------------	----------

MATERIAL AND DIMENSIONS

Dimensions	163 x 163 x 36 mm
Net weight	330 g
Color	White
COMMUNICATION	
IP	Sí
GPRS	Sí
Communication with CRA	Yes
AMBIENT	
Operating temperature	-10 °C ~ 40 °C
Use	Indoor
ZONES	
Maximum number of rooms	50
Maximum number of devices	100
PROCCESSOR	
Processor	ARM
Operating system	OS Malevich

PARTITIONS AND MEMORIES



