



P ▲ R ▲ D O X

Wireless volumetric detector

NV75MR

DETECTION

Detector type	Wireless
Detection distance	16 m
Angle detection	90°
Installation height	2.1 m ~ 2.7 m
Detection method	Infrared
Coverage	16 x 16 m
Pets immunity	Up to 50 cm
Antimasking	Sí
Anti-cloaking technology (activation of alarm after infrared detection AND / OR microwave)	Sí
PIR detection advance at ground level (PIR Creep)	Sí
Detection technology	Volumetric

ESPECIFICACIONES TÉCNICAS

Compatibility	Magellan panels
LED indicators	Sí
Tamper	Sí

AMBIENT

Operating temperature	-35 °C ~ 50 °C
Use	Indoor

TRASMISSIONE WIRELESS

Frequency	868MHz
-----------	---------------

CERTIFICATION

Grade	3
Normative	EN50131
Environmental class	II

POWER CONSUMPTION

Battery model	2 x AA
Battery duration	Up to 3 años

MATERIAL AND DIMENSIONS

Dimensions	128 x 62 x 54 mm
Net weight	120 g

LENS

Lens Type	Fresnel de segunda generación
-----------	--------------------------------------

SENSOR

Type of sensor	Dual
----------------	-------------

