


P ▲ R ▲ D O X



wired panel with 4 on-board zones

SP4000

COMMUNICATION

External voice module	Yes, with VDMP3 module
IP	Yes, with IP150 module
GPRS	Yes, with PCS module
GSM	Yes, with PCS module
RTC	Sí
Programming	Installer, teacher and maintenance
Expansion bus	Yes, 4 wires
Communication with CRA	Yes, through contactID and SIA

ZONES

Maximum number of zones	32
Keyboard areas	1
Wired on-board zones	4
ATZ (Double zones)	Sí, hasta 8 zonas
Maximum number of zones with expanders	24

POWER CONSUMPTION

Power mode	AC
Voltage	16.5V
Amperage	1200mA
Battery support	Entry available

PROGRAMMABLE OUTPUTS

Board	1
Maximum of PGMs	16
siren	Sí
Telephone line	Sí

CERTIFICATION

Grade	2
Normative	EN50131

ADDITIONAL FEATURES

Calendar	Sí
Software Update	Sí
Mobile app	INSITE GOLD
SMS notification	Sí
Call notification	Yes, with IP or PCS module (GPRS)

PARTITIONS AND MEMORIES

Partitions	2
User codes	32
Registration events	256
Maximum users	32

AMBIENT

Operating temperature	0 °C ~ 50 °C
Use	Indoor

MATERIAL AND DIMENSIONS

Dimensions	25.5 x 20 x 7.6 mm
Net weight	10 g

GENERAL INFORMATION

Type of Central	Wired
-----------------	-------

