technical datasheet



XMV

Wireless panel

HUB2-W

ADDITIONAL FEATURES

Mobile app	Ajax Security System	
SMS notification	Sí	
Call notification	Sí	
Notificación Push	Sí	
Maximum number of connected IP cameras	25	
Mobile devices	iOS 9.1 or later / Android 4.1 or later	
SIM card number	2	

POWER CONSUMPTION

Power mode	AC
Voltage	110V ~ 240V
Consumption (w)	10W
Battery life	± 16 hours
Battery support	Li-ion 2 A/h
Frequency	50 Hz / 60 Hz

MATERIAL AND DIMENSIONS

Dimensions	163 x 163 x 36 mm
Material	ABS plastic
Net weight	360 g
Color	White

CERTIFICATION

Grade	2
Normative	EN50131

GENERAL INFORMATION

Type of Central	Wireless
-----------------	----------

SABOTAGE

Box tamper	Sí

COMMUNICATION

IP	Sí
GPRS	Sí
Communication with CRA	Yes, through contactID and SIA
Protocolo	Jeweller
2G	Yes

VIA RADIO

Frequency	868mHz
Transmission distance	Up to 2000 m (without obstacles)
Maximum	Class 4 (2W) / 850/900Mhz , Class 2
power RF	(1W) / 1800/1900MHz

AMBIENT

Operating temperature	-10 °C ~ 40 °C
Use	Indoor

ZONES

Maximum number of rooms	50
Maximum number of devices	100

PARTITIONS AND MEMORIES

Maximum users	50
---------------	----

PROCCESSOR

Operating system OS Malevich

