technical datasheet



XMV

Wireless panel HUB2-B

ADDITIONAL FEATURES

Mobile app	Ajax Security System
SMS notification	Sí
Call notification	Sí
Notificación Push	Sí
Maximum number of connected IP cameras	25
Mobile devices	iOS 9.1 or later / Android 4.1 or later
SIM card number	2

POWER CONSUMPTION

Power mode	AC
Voltage	110V ~ 240V
Consumption (w)	10W
Battery life	± 16 hours
Battery support	Li-ion 2 A/h
Frequency	50 Hz / 60 Hz

MATERIAL AND DIMENSIONS

Dimensions	163 x 163 x 36 mm
Material	ABS plastic
Net weight	360 g
Color	Black

ZONES

Maximum number of rooms	50
Maximum number of devices	100

PARTITIONS AND MEMORIES

Maximum users	50
---------------	----

SABOTAGE

Box tamper	Sí

COMMUNICATION

IP	Sí
GPRS	Sí
Communication with CRA	Yes, through contactID and SIA
Protocolo	Jeweller
2G	Yes

VIA RADIO

Frequency	868mHz
Transmission distance	Up to 2000 m (without obstacles)
Maximum	Class 4 (2W) / 850/900Mhz , Class 2
power RF	(1W) / 1800/1900MHz

AMBIENT

Operating temperature	-10 °C ~ 40 °C
Use	Indoor

SPECS AND FEATURES

Type of Central Wireless

CERTIFICATION

Grade 2

PROCCESSOR

Operating system OS Malevich

