



## Wired volumetric detector

### VXI-ST

#### DETECTION

|                      |                          |
|----------------------|--------------------------|
| Detector type        | <b>Wired</b>             |
| Detection distance   | <b>12 m</b>              |
| Angle detection      | <b>90°</b>               |
| Installation height  | <b>1.2 m</b>             |
| Detection method     | <b>Infrared</b>          |
| PIR coverage         | <b>2.5 m ~ 12 m</b>      |
| Detection speed      | <b>0,3 m/s ~ 1,5 m/s</b> |
| Pets immunity        | <b>Sí</b>                |
| Antimasking          | <b>Sí</b>                |
| Alarm period         | <b>2.0 ± 1 s</b>         |
| Detection technology | <b>Volumetric</b>        |

#### SENSOR

|                        |                          |
|------------------------|--------------------------|
| Type of sensor         | <b>PIR</b>               |
| Double PIR sensor      | <b>Sí</b>                |
| Sensitivity adjustment | <b>Sí</b>                |
| RF interference        | <b>No alarm 10 V / m</b> |

#### MATERIAL AND DIMENSIONS

|              |                               |
|--------------|-------------------------------|
| Installation | <b>Wall / Post</b>            |
| Dimensions   | <b>181.9 x 70.9 x 64.5 mm</b> |
| Net weight   | <b>500 g</b>                  |

#### AMBIENT

|                       |                       |
|-----------------------|-----------------------|
| Operating temperature | <b>-30 °C ~ 60 °C</b> |
| Degree of protection  | <b>IP55</b>           |
| Use                   | <b>Outdoor</b>        |
| Maximum humidity      | <b>95%</b>            |

#### POWER CONSUMPTION

|            |              |
|------------|--------------|
| Power mode | <b>DC</b>    |
| Voltage    | <b>28V</b>   |
| Amperage   | <b>100mA</b> |

#### ESPECIFICACIONES TÉCNICAS

|                |             |
|----------------|-------------|
| LED indicators | <b>1</b>    |
| LED colors     | <b>Rojo</b> |

