



5 in 1 (hd-cvi, hd-tvi, ahd, analog and ip) recorder of 4 channel and 4 mpx maximum resolution

HWD-6104MH-G3A

RECORDING

Maximum recording resolution	4 Mpx
Video compression	H.265 / H.264
Resolution HDCVI recording	4 Megapíxeles
Resolution HDTVI recording	4 Megapíxeles
Resolution recording AHD	4 Megapíxeles
Images per second Main stream	4Mpx (8fps) / 4Mpx Lite / 1080P / 720P / WD1 / 4CIF / VGA / CIF (15fps)
Images per second Extra stream	WD1 / 4CIF / 2CIF (12fps) / CIF / QVGA / QCIF (25fps)
Video bit rate	32 Kbps ~ 6 Mbps
Audio compression	G.711U
Speed audio bits	64Kbps per channel

VIDEO

BNC channels	4
IP Channels	6, replacing the BNC channels
Accepted IP cameras	4 BNC cameras + 2 IP cameras
Video formats	HDCVI / TVI / AHD / CVBS / IP
Admitted resolutions HDCVI	4Mpx / 2mpx / 1Mpx
Admitted resolutions HDTVI	4Mpx / 2Mpx / 1Mpx
Admitted resolutions AHD	4Mpx / 2Mpx / 1Mpx
Cameras CVBS	Yes
Resolution IP cameras	6 Megapíxeles

VIDEO OUTPUT

HDMI Output Number	1
Number of VGA outputs	1
Resolution HDMI	1080P
Resolución VGA	1080P

MATERIAL AND DIMENSIONS

NETWORK FEATURES

Number of ports RJ45	1
Velocità RJ45	10 / 100 Mbps
Maximum number of users	32
Mobile devices	Android / IOS (Apple)
ONVIF	Yes
Remote vision	Web Browser / Smartphone App and Hik-Connect Software.
Software	IVMS
App	Hik-Connect

POWER CONSUMPTION

Power mode	DC
Voltage	12V
Consumption (w)	8W
Amperage	670mA

AMBIENT

Operating temperature	-10 °C ~ 55 °C
Use	Indoor
Maximum humidity	90%

INPUTS/OUTPUTS

Alarm input	4
USB 2.0	2
Alarm output	1

STORAGE

Number of supported hard drives	1
Maximum hard disk size (Unit)	10 TB
Type HDD	3,5 SATA"

REPRODUCTION AND COPY OF SECURITY

Búsqueda inteligente	Yes
Synchronized playback	4

technical datasheet

Dimensions **260 x 222 x 45 mm**

Material **Metal**

Net weight **800 g**

AUDIO

Audio Inputs **1**

Audio Outputs **1**

Audio bidirectional (Full-duplex) **Yes**

GENERAL INFORMATION

Serie **HiWatch**

Technology **5 IN 1 (HD-CVI, HD-TVI, AHD, analog and IP)**

