



## AJAX

### Wireless volumetric double technology detector

### MOTIONCAMOUTDOOR-W

#### DETECTION

|                      |                                      |
|----------------------|--------------------------------------|
| Detector type        | <b>Wireless</b>                      |
| Installation height  | <b>0.8 m ~ 1.3 m</b>                 |
| Angle detection      | <b>90° horizontal / 80° vertical</b> |
| Detection distance   | <b>Adjustable 3m ~ 15m</b>           |
| Pets immunity        | <b>Up to 80 cm</b>                   |
| Antimasking          | <b>Yes</b>                           |
| Detection technology | <b>Volumetric double technology</b>  |

#### MATERIAL AND DIMENSIONS

|                       |                          |
|-----------------------|--------------------------|
| Installation          | <b>Surface</b>           |
| Dimensions            | <b>206 x 108 x 93 mm</b> |
| Net weight            | <b>470 g</b>             |
| Weight with packaging | <b>750 g</b>             |
| Color                 | <b>White</b>             |

#### TECHNICAL SPECIFICATIONS

|                                 |                                  |
|---------------------------------|----------------------------------|
| LED indicators                  | <b>Yes</b>                       |
| Tamper                          | <b>Yes</b>                       |
| Protection against false alarms | <b>Yes, algorithmic analysis</b> |

#### VERIFICACIÓN FOTOGRÁFICA

|                           |                                        |
|---------------------------|----------------------------------------|
| Picture quality           | <b>320 x 176 (default) / 640 x 352</b> |
| Reception time of a photo | <b>Up to 9 sec</b>                     |
| Series images             | <b>2 - 5 images</b>                    |

#### CERTIFICATION

|           |                |
|-----------|----------------|
| Grade     | <b>2</b>       |
| Normative | <b>EN50131</b> |

#### AMBIENT

|                       |                       |
|-----------------------|-----------------------|
| Operating temperature | <b>-25 °C ~ 60 °C</b> |
| Degree of protection  | <b>IP55</b>           |
| Use                   | <b>Indoor-outdoor</b> |
| Maximum humidity      | <b>95%</b>            |

#### VIA RADIO

|                       |                                         |
|-----------------------|-----------------------------------------|
| Frequency             | <b>868.0 MHz ~ 868.6 MHz</b>            |
| Transmission distance | <b>Up to 1700 m (without obstacles)</b> |
| Maximum power RF      | <b>Hasta 20 mW</b>                      |

#### SENSOR

|                        |                                     |
|------------------------|-------------------------------------|
| Type of sensor         | <b>2 x passive infrared sensors</b> |
| Double PIR sensor      | <b>Sí</b>                           |
| Sensitivity adjustment | <b>Sí</b>                           |

#### POWER CONSUMPTION

|                  |                        |
|------------------|------------------------|
| Battery model    | <b>4 x CR123A / 6V</b> |
| Battery duration | <b>Up to 3 años</b>    |

#### GENERAL INFORMATION

|               |                           |
|---------------|---------------------------|
| Compatibility | <b>Hub 2 / Hub 2 Plus</b> |
|---------------|---------------------------|

