



## Minidome hd-cvi camera of 8 megapíxeles and fix lens

HAC-HDW1800TL-A

### VIDEO (CAMERAS)

|                   |                                                 |
|-------------------|-------------------------------------------------|
| Video Resolution  | 8 Megapixels                                    |
| BLC               | Yes                                             |
| HLC               | Yes                                             |
| 2D-NR             | Yes                                             |
| AGC               | Yes                                             |
| AWB               | Yes                                             |
| WDR               | DWDR                                            |
| Images per second | 25fps                                           |
| Video output      | 1 x BNC switchable HD-CVI / HD-TVI / AHD / CVBS |
| Day / night mode  | Automatic                                       |
| OSD menu          | Yes                                             |
| Privacy mask      | Up to 8 zones                                   |
| Mirror            | On / Off                                        |

### NIGHT VISION

|                       |                    |
|-----------------------|--------------------|
| Night vision distance | 30 m               |
| Type of night vision  | IR                 |
| Number of LEDs        | 1                  |
| IR ON/Off             | Automatic / Manual |
| Smart IR              | Yes                |

### POWER CONSUMPTION

|                 |       |
|-----------------|-------|
| Power mode      | DC    |
| Voltage         | 12V   |
| Consumption (w) | 4.3W  |
| Amperage        | 360mA |

### MATERIAL AND DIMENSIONS

|                       |                   |
|-----------------------|-------------------|
| Dimensions            | 85.8 x 97 (Ø) mm  |
| Material              | Metal and plastic |
| Net weight            | 300 g             |
| Weight with packaging | 380 g             |

### GENERAL INFORMATION

|       |      |
|-------|------|
| Serie | LITE |
|-------|------|

### IMAGE

|                          |                  |
|--------------------------|------------------|
| Sensor                   | CMOS ®           |
| Sensor resolution        | 3840 x 2160      |
| Sensor Size              | 1/2.7"           |
| Electronic shutter speed | 1/25 ~ 1/100000s |
| Minimum lighting         | 0.03Lux          |
| Ratio S / N              | More than 65dB   |

### LENS

|                           |        |
|---------------------------|--------|
| Lens Type                 | Fix    |
| Focal distance            | 2.8 mm |
| Maximum diaphragm opening | F/2.0  |
| Angle of View             | 105°   |
| Minimum focus distance    | 1000mm |

### AMBIENT

|                       |                |
|-----------------------|----------------|
| Operating temperature | -40 °C ~ 60 °C |
| Degree of protection  | IP67           |
| Use                   | Indoor-outdoor |
| Maximum humidity      | 95%            |

### DISTANCE DORI

|           |      |
|-----------|------|
| Detect    | 75 m |
| Observe   | 30 m |
| Recognize | 15 m |
| Identify  | 8 m  |

### AXES

|        |        |
|--------|--------|
| Motion | 3-Axis |
|--------|--------|

### AUDIO(CAMERAS)

|                     |     |
|---------------------|-----|
| Built in microphone | Yes |
|---------------------|-----|

# technical datasheet

Technology

HD-CVI

Type of camera

Minidome

