



HIKVISION
HiWatch Series

Minidome ip camera of 4 megapixels and fix lens

HWI-D140H

VIDEO (CAMERAS)

Resolución vídeo	4 Megapixels
BLC	Yes
3D-NR	Yes
AGC	Yes
AWB	Yes
WDR	WDR (120 dB)
Images per second	20fps
Video output	RJ45
Day / night mode	Automatic / Manual
Privacy mask	Yes
Bit rate	32Kbps ~ 8Mbps
Compression	H.265+ / H.265 / H.264
Main stream	4Mpx (1 ~ 20fps) / 3Mpx / 1080P / 720P (1 ~ 25fps)
Sub stream	640 × 480 / 640 × 360 (1 ~ 25fps)
Watermark	Yes
Anti flap	Yes
Mirror	On / Off

POWER CONSUMPTION

Power mode	DC
Voltage	12V
Consumption (w)	6.5W
Amperage	400mA
PoE power	Yes
Type PoE	PoE 802.3af

LENS

Lens Type	Fix
Focal distance	2.8 mm
Maximum diaphragm opening	F/2.0
Angle of View	98°
Filtro IR	Si

DISTANCE DORI

NETWORK FEATURES

IP connection	1 RJ45 (10M / 100M)
ONVIF	Yes
Maximum number of users	Up to 32 users
Password protection	Yes
Web browser	Explorer / Chrome / Firefox
Management software	iVMS-4200 / Hik-Connect
Mobile devices	Android / IOS (Apple)
Live view	Up to 6 channels
IP address filter	Yes

IMAGE

Sensor	CMOS ®
Resolución sensor	2560 x 1440
Sensor Size	1/3'
Electronic shutter speed	1/3 ~ 1/100000s
Minimum lighting	0.01Lux

AMBIENT

Operating temperature	-30 °C ~ 60 °C
Degree of protection	IP67
Anti vandal	IK10
Use	Indoor-outdoor
Maximum humidity	95%

MATERIAL AND DIMENSIONS

Dimensions	82.4 x 111 (Ø) mm
Material	Aluminum
Net weight	360 g
Weight with packaging	560 g

NIGHT VISION

Night vision distance	30 m
Type of night vision	IR
Wavelength	850 nm

AXES

technical datasheet

Detect	62 m
Observe	25 m
Recognize	12 m
Identify	6 m

SPECS AND FEATURES

Serie	HiWatch
Technology	IP
Type of camera	Minidome

VIDEO ANALYSIS

Tipo de deteccion	Detección de movimiento básica (diferencia de píxeles)
Motion detection	Yes
Video Tamper	Sí

Motion

2-Axis

STORAGE

Storage Systems

NAS / FTP

