

Milesight



Bullet ip camera of 5 megapixels and fix lens

MS-C5364-PD

VIDEO (CAMERAS)

Video Resolution	5 Megapixels
BLC	Yes
HLC	Yes
3D-NR	Yes
AGC	Yes
AWB	Yes
WDR	WDR (120 dB)
Images per second	25fps
Video output	RJ45
Day / night mode	Automatic / Manual
Privacy mask	Up to 4 zones
Anti fog system	Yes
Type of Codex	CBR / VBR
Bit rate	16Kbps ~ 16Mbps
Compression	H.265+ / H.265 / H.264
Main stream	5Mpx / 3Mpx / 1080P / 1.3Mpx / 720P / 704 x 576 (1 ~ 25fps)
Sub stream	704 x 576 / 640 x 480 / 640 x 360 / 352 x 288 (1 ~ 25fps)
Sub stream 2	1080P / 720P / 704 x 576 / 640 x 480 / 640 x 360 / 352 x 288 (1 ~ 25fps)
Watermark	Yes
Anti flap	Yes

IMAGE

Sensor	CMOS ®
Sensor resolution	2592 x 1944
Sensor Size	1/2.8"
Electronic shutter speed	1s to 1/100,000s
Minimum lighting	0.005Lux
Ratio S / N	More than 55dB

NETWORK FEATURES

IP connection	1 RJ45 (10M / 100M)
ONVIF	Yes, type S, G, T and Q

VIDEO ANALYSIS

Detection type	Analytical with human/vehicle classification in line/area crossing
AI Functions	People counting
Crossing line	Yes
Motion detection	Yes
Abandoned object	Yes
Missing object	Yes
Video Tamper	Yes
People counting	Yes
Loitering detection	Yes
Classification Human / vehicle	Yes

AMBIENT

Operating temperature	-40 °C ~ 60 °C
Degree of protection	IP67
Anti vandal	IK10
Use	Indoor-outdoor
Maximum humidity	90%

LENS

Lens Type	Fix
Focal distance	2.8 mm
Maximum diaphragm opening	F/1.6
Angle of View	105°

DISTANCE DORI

Detect	59 m
Observe	23 m
Recognize	12 m
Identify	6 m

POWER CONSUMPTION

Consumption (w)	5.4W
PoE power	Yes
Type PoE	PoE 802.3af

STORAGE

technical datasheet

Management software	Milesight CMS
IP address filter	Yes
Network disconnection	Yes

GENERAL INFORMATION

Serie	AI Mini Camera Series
Technology	IP
Type of camera	Bullet

NIGHT VISION

Night vision distance	30 m
Type of night vision	IR
Starlight	Yes

MATERIAL AND DIMENSIONS

Dimensions	160 x 64 (Ø) mm
Net weight	450 g

MicroSD-Card	Up to 256Gb
Storage Systems	NAS / Micro SD / Recorder
ANR (Redundant Recording in SD)	Yes

AXES

Motion	3-Axis
--------	---------------

