# technical datasheet



# XMV

# Wireless panel HUB2-4G-B

# **ADDITIONAL FEATURES**

Mobile app	Ajax Security System
SMS notification	Sí
Call notification	Sí
Notificación Push	Sí
Maximum number of connected IP cameras	25
SIM card number	2
LED indicators	Yes

#### POWER CONSUMPTION

Power mode	AC
Voltage	110V ~ 240V
Consumption (w)	10W
Battery life	± 16 hours
Battery support	Li-ion 2 A/h

# MATERIAL AND DIMENSIONS

Dimensions	163 x 163 x 36 mm
Material	ABS plastic
Net weight	360 g
Color	Black

# VIA RADIO

Frequency	868.0 MHz ~ 868.6 MHz
Transmission	Up to 2000 m (without
distance	obstacles)

# **GENERAL INFORMATION**

Type of Central Wireless

#### SABOTAGE

Box tamper Sí

# COMMUNICATION

Communication with CRA	Yes, through contactID and SIA
Protocolo	Jeweller / Wings
Ethernet	Yes
2G/3G	Yes
4G	Yes

#### **AMBIENT**

Operating temperature	-10 °C ~ 40 °C	
Use	Indoor	
Maximum humidity	75%	

# CERTIFICATION

Grade	2
Normative	EN50131

# **ZONES**

Maximum number of rooms	50
Maximum number of devices	100

### PARTITIONS AND MEMORIES

Maximum users	50
Maxilliulli usels	50

#### **PROCCESSOR**

Operating system OS Malevich

