technical datasheet



X

Wireless panel HUB2-4G-B

ADDITIONAL FEATURES

Mobile app	Ajax Security System
SMS notification	Sí
Call notification	Sí
Notificación Push	Sí
Maximum number of connected IP cameras	25
SIM card number	2
LED indicators	Yes

POWER CONSUMPTION

Power mode	AC
Voltage	110V ~ 240V
Consumption (w)	10W
Battery life	± 16 hours
Battery support	Li-ion 2 A/h

MATERIAL AND DIMENSIONS

Dimensions	163 x 163 x 36 mm
Material	ABS plastic
Net weight	360 g
Color	Black

VIA RADIO

868.0 MHz ~ 868.6 MHz
Up to 2000 m (without
obstacles)

GENERAL INFORMATION

Type of Central	Wireless
Type of certifian	*****

SABOTAGE

Box tamper	Sí
------------	----

COMMUNICATION

Communication with CRA	Yes, through contactID and SIA
Protocolo	Jeweller / Wings
2G/3G	Yes
4G	Yes
Ethernet	Yes

AMBIENT

Operating temperature	-10 °C ~ 40 °C
Use	Indoor
Maximum humidity	75 %

ZONES

Maximum number of rooms	50
Maximum number of devices	100

CERTIFICATION

Grade	2
Normative	EN50131

PARTITIONS AND MEMORIES

Maximum users 50

PROCCESSOR

Operating system OS Malevich

