

Milesight



Ip recorder of 16 channel and 12 mpx resolution with 16 PoE ports

MS-N7016-UPH

RECORDING

Maximum recording resolution	12 Mpx
Input bandwidth	160Mbps
Video compression	H.265+ / H.265 / H.264+ / H.264
Recording mode	Continuous / Event (motion detection, alarm, VCA, Smart analysis)
Audio compression	G.711 / G.722 / G.726 / AAC
Frecuencia muestreo audio	8KHz / 16KHz
Resolutions	12Mpx / 4K / 6Mpx / 5Mpx / 4Mpx / 3Mpx / 1080P / UXGA / 720P / D1 / VGA / CIF / QCIF
ANR (Redundant Recording in SD)	Sí
Output bandwidth	160Mbps

NETWORK FEATURES

PoE ports	16
Number of ports RJ45	1
Velocità RJ45	10 / 100 / 1000 Mbps
ONVIF	Yes
Type PoE	802.3at / af
PoE consumption	200W
Software	Milesight CMS

INPUTS/OUTPUTS

Alarm input	16
USB 2.0	2
USB 3.0	1
RS232	1
RS485	2
Alarm output	4

STORAGE

Number of supported hard drives	4
---------------------------------	---

MATERIAL AND DIMENSIONS

Installation	Rack
Dimensions	440 x 320 x 66.8 mm
Material	Metal
Net weight	5000 g
Weight with packaging	6200 g
Chassis	1.5U

INTELLIGENT VIDEO SYSTEM

People counting	Sí
Motion detection	Yes
Video Tamper	Yes
Loitering detection	Yes
ANPR	Yes

VIDEO OUTPUT

HDMI Output Number	1
Number of VGA outputs	1
Resolution HDMI	4K
Resolución VGA	1080P

POWER CONSUMPTION

Power mode	AC
Voltage	100V ~ 240V
Consumption (w)	20W

GENERAL INFORMATION

Serie	4K PoE Series
Technology	IP

AUDIO

Audio Inputs	1
Audio Outputs	1

technical datasheet

Maximum hard disk size (Unit)	10 TB
Type HDD	3,5 SATA"
Raid	0 / 1 / 5 / 6 / 10

AMBIENT

Operating temperature	-10 °C ~ 55 °C
Use	Indoor
Maximum humidity	90%

VIDEO

IP Channels	16
Resolution IP cameras	8 Megapíxeles

