



AJAX

Hybrid panel

HUBHYBRID-FIBRA-B

ADDITIONAL FEATURES

Mobile app	Ajax Security System
SMS notification	Sí
Call notification	Sí
Notificación Push	Sí
Maximum number of connected IP cameras	25
SIM card number	2

POWER CONSUMPTION

Power mode	AC
Voltage	110V ~ 240V
Consumption (w)	10W
Built in battery	Not
Battery model	12V DC 4 ~7Ah

AMBIENT

Operating temperature	-10 °C ~ 40 °C
Degree of protection	IP50
Use	Indoor
Maximum humidity	75%

ZONES

Maximum number of rooms	50
Maximum number of devices	100
Automated scenarios	32

CERTIFICATION

Grade	3
Normative	EN50131
Environmental class	II

SABOTAGE

Box tamper	Sí
------------	-----------

MATERIAL AND DIMENSIONS

Dimensions	196 x 238 x 100 mm
Material	Plastic
Net weight	720 g
Weight with packaging	1130 g
Color	Black

COMMUNICATION

IP	Sí
Protocolo	Jeweller / Wings / Fibra (BUS)
Mobile Network	2G
Number of BUS inputs	8

VIA RADIO

Frequency	868.0 MHz ~ 868.6 MHz
Maximum power RF	Hasta 20 mW
Maximum distance between the device and the hub	2000 m

PARTITIONS AND MEMORIES

Partitions	9
Maximum users	50

SPECS AND FEATURES

Type of Central	Hybrid
-----------------	---------------

