



## Wired volumetric detector VXI-DAM-X5

### DETECTION

Detector type	<b>Wired</b>
Detection distance	<b>12 m</b>
Angle detection	<b>90°</b>
Installation height	<b>0.8 m ~ 1.2 m</b>
PIR coverage	<b>2.5 m ~ 12 m</b>
Detection speed	<b>0,3 m/s ~ 1,5 m/s</b>
Detection zones	<b>16</b>
Antimasking	<b>Sí</b>
Alarm period	<b>2.0 ± 1 s</b>
Detection technology	<b>Volumetric</b>

### SENSOR

Type of sensor	<b>PIR and microwave</b>
Sensitivity adjustment	<b>Interruptores DIP</b>
Microwave	<b>10.525 GHz</b>
RF interference	<b>No alarm 10 V / m</b>

### MATERIAL AND DIMENSIONS

Dimensions	<b>81.6 x 199.3 x 70.3 mm</b>
Net weight	<b>380 g</b>
Weight with packaging	<b>510 g</b>

### AMBIENT

Operating temperature	<b>-20 °C ~ 45 °C</b>
Degree of protection	<b>IP55</b>
Use	<b>Indoor-outdoor</b>
Maximum humidity	<b>95%</b>

### POWER CONSUMPTION

Power mode	<b>DC</b>
Voltage	<b>9.5V ~ 18V</b>
Amperage	<b>35mA</b>

### ESPECIFICACIONES TÉCNICAS

LED indicators	<b>Yes, Warm up, alarm, masking detection</b>
Tamper	<b>Sí</b>
Start time	<b>60 s</b>

