

HIKVISION®



Ip recorder of 32 channel and 32 mpx resolution

DS-7732NXI-I4/S

RECORDING

Maximum recording resolution	32 Mpx
Input bandwidth	256Mbps
Video compression	H.265+ / H.265 / H.264+ / H.264
Channels that support the maximum recording resolution	32 Mpx y 24 Mpx solo en canal 1 cuando el modo Ultra HD esté activado
Audio compression	G.711A / G.711U / G.722 / G.726 / MP2L2
Resolutions	32Mpx / 24Mpx / 12Mpx / 4K / 6Mpx / 5Mpx / 4Mpx / 3Mpx / 1080P / UXGA / 720P / VGA / 4CIF / DCIF / 2CIF / CIF / QCIF
Output bandwidth	256Mbps

VIDEO OUTPUT

HDMI Output Number	2
Number of VGA outputs	1
Number of BNC outputs	1
Resolution HDMI	4K / 1080P
VGA resolution	1080P
Resolution BNC	704 x 576
Similar video signals	HDMI and VGA

MATERIAL AND DIMENSIONS

Installation	Rack
Dimensions	445 x 400 x 75 mm
Material	Metal
Net weight	4200 g
Weight with packaging	6000 g
Chassis	1.5U

STORAGE

Number of supported hard drives	4
Maximum hard disk size (Unit)	10 TB
Type HDD	3,5 SATA"
eSata	Sí

NETWORK FEATURES

Number of ports RJ45	2
Speed RJ45	10 / 100 / 1000 Mbps
Maximum number of users	128
Mobile devices	Android / IOS (Apple)
Remote vision	Web Browser / Smartphone App and Hik-Connect Software.
Software	IVMS
App	Hik-Connect

INPUTS/OUTPUTS

Alarm input	16
USB 2.0	2
USB 3.0	1
RS232	1
RS485	1
Alarm output	4

POWER CONSUMPTION

Power mode	AC
Voltage	100V ~ 240V
Consumption (w)	30W

AMBIENT

Operating temperature	-10 °C ~ 55 °C
Use	Indoor
Maximum humidity	90%

INTELLIGENT VIDEO SYSTEM

POS	Yes
VCA	Sí
Motion detection	Yes, 32 channels

REPRODUCTION AND COPY OF SECURITY

Simultaneous cameras in reproduction	1 / 2 / 4 / 6 / 8 / 9 / 16 / 25 / 32 / 36
Synchronized playback	16

FACE RECOGNITION

AUDIO

Audio Inputs	1
Audio Outputs	1
Audio bidirectional (Full-duplex)	Yes

GENERAL INFORMATION

Serie	Acusense
Technology	IP

PERIMETER PROTECTION

Channels number with analytics	4 channels / 12 IVS rules for each channel
Type of identification	Human secondary recognition / vehicle for line crossing and intrusion

VIDEO

IP Channels	32
-------------	----

Number of channels with facial recognition

1 channel video face recognition / 4 channels facial photo recognition

Database management

Up to 16 databases with 10,000 faces in total / Allows designating name / gender / birth date / nationality / address / Identification information can be added to each face image

