



DAHUA

VTO4202FB-P-S2

CAMERA

Resolution	2 Mpx
Sensor	CMOS
Sensor size	1/2.5"
Focal distance	1.9mm
Horizontal viewing angle	169°
Diagonal angle of view	177°
Night vision	SI
Day / Night	ICR
Video compression	H.265

POWER CONSUMPTION

Power mode	DC
Voltage	48V
Consumption (w)	12W
Amperage	1000mA
PoE power	Yes
Type PoE	PoE 802.3af
Power output	1 12V / 100mA

INPUTS/OUTPUTS

RS485	1
Door sensor	1
Exit button	1
Alarm output	1

NETWORK CHARACTERISTICS (INTERCOM MONITORS)

Network protocol	SIP / P2P / IPv4 / UPnP / SNMP / DNS / DDNS / RTSP / RTP / TCP / UDP
IP connection	10M/100Mbps
ONVIF	Yes

GENERAL INFORMATION

Technology	2 Wires / IP
------------	--------------

AMBIENT

Operating temperature	-30 °C ~ 60 °C
Degree of protection	IP65
Anti vandal	IK07
Use	Indoor-outdoor
Maximum humidity	90%

MATERIAL AND DIMENSIONS

Installation	Surface / embed
Dimensions	100 x 100 x 49.3 mm
Net weight	300 g
Weight with packaging	450 g
Color	Black

AUDIO (VIDEO INTERCOM)

Sound input	1
Sound output	Built-in speaker
Bidirectional audio	SI
Audio compression	G.711A/G.711U/PCM

SYSTEM (RECORDERS)

Processor	Embedded Processor
Operating system	Embedded LINUX

GENERAL CHARACTERISTICS (VIDEO INTERCOM)

Led indicator	SI, 3
---------------	-------

