



28 ports switch with 24 PoE ports

VK-SWITCH-2824POE-400-G-L2

CHARACTERISTICS (SWITCH)

Data rate supported	192 Gbps
Packet redirection speed	41.7 Mpps
VLAN	Yes, up to 4K
DHCP	Sí
Maximum transmission distance	100 m
Buffer Memory	4.1 Mb
Manageable	Sí, tipo L2
Web configuration	Sí
Mirror port	Yes, bidirectional
Spanning Tree	Yes, STP / RSTP / MSTP
QoS	Yes, 802.1p
Port Aggregation	LACP / Static aggregation (max. 14 groups and 8 ports per group)
Enrutamiento estático	Yes, max. 128 rules
SSH	2.0
RADIUS AAA	Yes

MATERIAL AND DIMENSIONS

Installation	Desk / Rack
Dimensions	440 x 290 x 44.5 mm
Material	Metal
Net weight	3900 g
Weight with packaging	4700 g
Chassis	1U

AMBIENT

Operating temperature	-20 °C ~ 55 °C
Degree of protection	IP30
Use	Indoor
Maximum humidity	90%
Lightning protection	4KV

SYSTEM (SWITCH)

MAC address table	8K
-------------------	----

POWER CONSUMPTION

Power mode	AC
Voltage	100V ~ 240V
Amperage	5000mA
Standby consumption	18W
Consumption On	380W
Maximum consumption per port (PoE)	30W
Total maximum consumption (PoE)	400W
Power supply included	Yes

ETHERNET PORTS

POE ports	24
Fiber port	4 x 100/1000
10 / 100 / 1000 Base-T	24
POE Ports Speed	10 / 100 / 1000
Uplink ports speed	No dispone
Number of Ethernet ports	28

NET STANDARD

IEEE802,3af	Sí
IEEE802,3at	Sí

ADDITIONAL FEATURES

Console port	Yes (cable included)
--------------	----------------------

