

HIKVISION®

Ip recorder of 16 channel and 12
mpx resolution

DS-7616NXI-K2/16P

**NETWORK FEATURES**

PoE ports	16
Number of ports RJ45	1
Velocità RJ45	10 / 100 / 1000 Mbps
Maximum number of users	128
Mobile devices	Android / IOS (Apple)
ONVIF	Yes
Remote vision	Web Browser / Smartphone App and Hik-Connect Software.
Type PoE	802.3at / af
PoE consumption	200W
Software	IVMS
App	Hik-Connect

MATERIAL AND DIMENSIONS

Installation	Desk / Rack
Dimensions	385 x 315 x 52 mm
Material	Metal
Net weight	2600 g
Weight with packaging	3530 g

POWER CONSUMPTION

Power mode	AC
Voltage	100V ~ 240V
Consumption (w)	15W

AUDIO

Audio Inputs	1
Audio Outputs	1
Audio bidirectional (Full-duplex)	Yes

INPUTS/OUTPUTS

Alarm input	4
USB 2.0	2
Alarm output	1

VIDEO

IP Channels	16
-------------	-----------

RECORDING

Maximum recording resolution	12 Mpx
Input bandwidth	160Mbps
Video compression	H.265+ / H.265 / H.264+ / H.264
Audio compression	G.711A / G.711U / G.722 / G.726 / AAC
Resolutions	12Mpx / 4K / 6Mpx / 5Mpx / 4Mpx / 3Mpx / 1080P / UXGA / 720P / VGA / 4CIF / DCIF / 2CIF / CIF / QCIF
Output bandwidth	160Mbps

VIDEO OUTPUT

HDMI Output Number	1
Number of VGA outputs	1
Resolution HDMI	4K
Resolución VGA	1080P
Independent video signals	Yes

AMBIENT

Operating temperature	-10 °C ~ 55 °C
Use	Indoor
Maximum humidity	90%

STORAGE

Number of supported hard drives	2
Maximum hard disk size (Unit)	10 TB
Type HDD	3,5 SATA"

GENERAL INFORMATION

Serie	Acusense
Technology	IP

INTELLIGENT VIDEO SYSTEM

Classification Human / vehicle	Yes
Motion detection	Yes, 2.0

REPRODUCTION AND COPY OF SECURITY

Synchronized playback	16
-----------------------	-----------

Resolution IP cameras **12 Megapíxeles**

FACE RECOGNITION

Number of channels with facial recognition **1 channel video face recognition / 4 channels facial photo recognition**

Database managment **Up to 16 databases with 20,000 faces in total**



PERIMETER PROTECTION

Channels number with analytics **2 channels**