

## A-CCTV



Bullet 4 in 1 (cvi, tvi, ahd and analog) camera of 5 megapixels and optical zoom lens

A-4N1-B50Z

## VIDEO (CAMERAS)

|                   |                                                        |
|-------------------|--------------------------------------------------------|
| Video Resolution  | <b>5 Megapixels</b>                                    |
| BLC               | <b>Yes</b>                                             |
| HLC               | <b>Yes</b>                                             |
| 2D-NR             | <b>Yes</b>                                             |
| AGC               | <b>Yes</b>                                             |
| AWB               | <b>Yes</b>                                             |
| WDR               | <b>DWDR</b>                                            |
| Images per second | <b>20fps</b>                                           |
| Video output      | <b>1 x BNC switchable HD-CVI / HD-TVI / AHD / CVBS</b> |
| Day / night mode  | <b>Automatic</b>                                       |
| OSD menu          | <b>Yes</b>                                             |
| Mirror            | <b>On / Off</b>                                        |

## DISTANCE DORI

|                         |              |
|-------------------------|--------------|
| Detect (Open lens)      | <b>64 m</b>  |
| Detect (Closed Lens)    | <b>178 m</b> |
| Observe (Open lens)     | <b>25 m</b>  |
| Observe (Closed lens)   | <b>70 m</b>  |
| Recognize (Open lens)   | <b>13 m</b>  |
| Recognize (Closed lens) | <b>35 m</b>  |
| Identify (Open lens)    | <b>6 m</b>   |
| Identify (Closed lens)  | <b>18 m</b>  |

## AMBIENT

|                       |                       |
|-----------------------|-----------------------|
| Operating temperature | <b>-30 °C ~ 50 °C</b> |
| Degree of protection  | <b>IP67</b>           |
| Use                   | <b>Indoor-outdoor</b> |
| Maximum humidity      | <b>90%</b>            |

## MATERIAL AND DIMENSIONS

|                       |                               |
|-----------------------|-------------------------------|
| Dimensions            | <b>217.7 x 80.5 x 80.5 mm</b> |
| Material              | <b>Metal</b>                  |
| Net weight            | <b>600 g</b>                  |
| Weight with packaging | <b>760 g</b>                  |

## IMAGE

|                   |                    |
|-------------------|--------------------|
| Sensor            | <b>CMOS ®</b>      |
| Sensor resolution | <b>2560 x 1936</b> |
| Sensor Size       | <b>1/2.7"</b>      |
| Minimum lighting  | <b>0.01Lux</b>     |
| Ratio S / N       | <b>Más de 52dB</b> |

## POWER CONSUMPTION

|                 |              |
|-----------------|--------------|
| Power mode      | <b>DC</b>    |
| Voltage         | <b>12V</b>   |
| Consumption (w) | <b>6W</b>    |
| Amperage        | <b>500mA</b> |

## NIGHT VISION

|                       |                           |
|-----------------------|---------------------------|
| Night vision distance | <b>50 m</b>               |
| Type of night vision  | <b>IR</b>                 |
| IR ON/Off             | <b>Automatic / Manual</b> |
| Smart IR              | <b>Yes</b>                |

## LENS

|                           |                       |
|---------------------------|-----------------------|
| Lens Type                 | <b>Optical zoom</b>   |
| Focal distance            | <b>2.8 mm ~ 12 mm</b> |
| Maximum diaphragm opening | <b>F/1.2</b>          |
| Angle of View             | <b>91.2° ~ 33.4°</b>  |

## GENERAL INFORMATION

|                |                                          |
|----------------|------------------------------------------|
| Technology     | <b>4 IN 1 (CVI, TVI, AHD and analog)</b> |
| Type of camera | <b>Bullet</b>                            |

## AXES

Motion

3-Axis

