

HIKVISION
HiWatch Series



Bullet ip camera of 4 megapixels and fix lens

HWI-B149HA

VIDEO (CAMERAS)

Resolución vídeo	4 Megapixels
BLC	Yes
HLC	Yes
3D-NR	Yes
AGC	Yes
AWB	Yes
WDR	WDR (120 dB)
Images per second	20fps
Video output	RJ45
Day / night mode	Colour
Privacy mask	Up to 4 zones
Type of Codex	CBR / VBR
Bit rate	32Kbps ~ 8Mbps
Compression	H.265+ / H.265 / H.264
Main stream	4Mpx (1 ~ 20fps) / 1080P / 720P (1 ~ 25fps)
Sub stream	720P / 640 x 480 / 640 x 360 (1 ~ 25fps)
Watermark	Yes
Mirror	On / Off

IMAGE

Sensor	CMOS ®
Resolución sensor	2560 x 1440
Sensor Size	1/3"
Electronic shutter speed	1/3 ~ 1/100000s
Minimum lighting	0.001Lux
Ratio S / N	Más de 52dB

NIGHT VISION

Night vision distance	30 m
Type of night vision	Luz blanca
IR ON/Off	Automatic / Manual
Full Color	Yes
White light	Sí

NETWORK FEATURES

IP connection	1 RJ45 (10M / 100M)
ONVIF	Yes, S and T type
Maximum number of users	Up to 32 users
Password protection	Yes
Web browser	Explorer / Chrome / Firefox
Management software	iVMS-4200 / Hik-Connect
Mobile devices	Android / IOS (Apple)
Live view	Up to 6 channels

POWER CONSUMPTION

Power mode	DC
Voltage	12V
Consumption (w)	5W
Amperage	400mA
PoE power	Yes
Type PoE	PoE 802.3af

LENS

Lens Type	Fix
Focal distance	2.8 mm
Maximum diaphragm opening	F/1.0
Angle of View	96°

AMBIENT

Operating temperature	-30 °C ~ 60 °C
Degree of protection	IP67
Use	Indoor-outdoor
Maximum humidity	95%

VIDEO ANALYSIS

Tipo de detección	Detección avanzada (clasificación persona/vehículo)
Video Tamper	Sí
Classification	Sí
Human / vehicle	
Motion detection	Yes (human and vehicle)
2.0	

technical datasheet

DISTANCE DATA

Detect	64 m
Observe	25 m
Recognize	12 m
Identify	6 m

MATERIAL AND DIMENSIONS

Dimensions	164.4 x 76.6 (Ø) mm
Material	Metal
Net weight	420 g
Weight with packaging	630 g

AXES

Motion	3-Axis
--------	---------------

GENERAL INFORMATION

Serie	ColorVu
Technology	IP
Type of camera	Bullet

STORAGE

Storage Systems	FTP
-----------------	------------

