



Remote controlled water shut-off valve

WATERSTOP-1/2-W



POWER CONSUMPTION

| | |
|------------------|---------------------|
| Power mode | DC |
| Voltage | 9V ~ 12V |
| Amperage | 2000mA |
| Built in battery | Yes |
| Battery model | 4 x CR123A |
| Battery duration | Up to 3 años |

CHARACTERISTICS (WATERSTOP)

| | |
|-------------------------|----------------------|
| Valve diameter | 1/2" |
| Closing time | Up to 5 sec |
| Maximum pressure | 10 bar |
| Water temperature | 5° C ~ 120° C |
| Manual control | Yes |
| Manageable by scenarios | Yes |

MATERIAL AND DIMENSIONS

| | |
|-----------------------|--------------------------|
| Dimensions | 140 x 104 x 70 mm |
| Net weight | 890 g |
| Weight with packaging | 1060 g |
| Color | White |

ESPECIFICACIONES TÉCNICAS

| | |
|--|-----------------------------|
| Compatibility | Centrales Ajax y Rex |
| LED indicators | Sí |
| Tamper | Sí |
| Tiempo de intervalo para la conexión con el receptor | 12 ~ 300 sec |

AMBIENT

| | |
|-----------------------|---------------------|
| Operating temperature | 0 °C ~ 60 °C |
| Degree of protection | IP56 |
| Use | Indoor |
| Maximum humidity | 95% |

VIA RADIO

| | |
|---|-------------------------------|
| Frequency | 868.0 MHz ~ 868.6 MHz |
| Maximum power RF | Hasta 20 mW |
| Maximum distance between the device and the hub | 1100 m (in open space) |
| Protocol | Jeweller |

GENERAL INFORMATION

Type **Remote controlled water shut-off valve**

