

HIKVISION®

Ip recorder of 8 channel and 12
mpx resolution

DS-7608NXI-K2

**NETWORK FEATURES**

Number of ports RJ45	1
Speed RJ45	10 / 100 / 1000 Mbps
Maximum number of users	128
Mobile devices	Android / IOS (Apple)
ONVIF	Yes
Remote vision	Web Browser / Smartphone App and Hik-Connect Software.
Software	IVMS
App	Hik-Connect

RECORDING

Maximum recording resolution	12 Mpx
Input bandwidth	80Mbps
Video compression	H.265+ / H.265 / H.264+ / H.264
Channels that support the maximum recording resolution	12MP only on 2 channels
Audio compression	G.711A / G.711U / G.722 / G.726 / AAC
Resolutions	12Mpx / 4K / 6Mpx / 5Mpx / 4Mpx / 3Mpx / 1080P / UXGA / 720P / VGA / 4CIF / DCIF / 2CIF / CIF / QCIF
Output bandwidth	160Mbps

VIDEO OUTPUT

HDMI Output Number	1
Number of VGA outputs	1
Resolution HDMI	4K
VGA resolution	1080P
Independent video signals	Yes

AMBIENT

Operating temperature	-10 °C ~ 55 °C
Use	Indoor
Maximum humidity	90%

STORAGE**MATERIAL AND DIMENSIONS**

Installation	Desk / Rack
Dimensions	385 x 315 x 52 mm
Material	Metal
Net weight	1720 g
Weight with packaging	2820 g
Chassis	1U

POWER CONSUMPTION

Power mode	DC
Voltage	12V
Consumption (w)	15W
Amperage	3300mA

INPUTS/OUTPUTS

Alarm input	4
USB 2.0	1
USB 3.0	1
Alarm output	1

AUDIO

Audio Inputs	1
Audio Outputs	1
Audio bidirectional (Full-duplex)	Yes

GENERAL INFORMATION

Serie	Acusense
Technology	IP

PERIMETER PROTECTION

Channels number with analytics	2 channels
Smart search	Search by classification (Human / Vehicle)

VIDEO

IP Channels	8
-------------	---

technical datasheet

STORAGE

Number of supported hard drives	2
Maximum hard disk size (Unit)	10 TB
Type HDD	3,5 SATA"

REPRODUCTION AND COPY OF SECURITY

Smart search	Yes
Synchronized playback	8

FACE RECOGNITION

Number of channels with facial recognition	1 channel video face recognition / 4 channels facial photo recognition
Database managment	Up to 16 databases with 20,000 faces in total

INTELLIGENT VIDEO SYSTEM

Motion detection	Yes, 2.0
------------------	----------

