

MOVOK
ACCESSORIES



Video / power supply passive
balun 2 unit

VK-BALUN-4K-DC

TRANSMISSION

Distancia de transmisión HDCVI 720p	440 m
Distancia de transmisión HDCVI 1080p	250 m
Distancia de transmisión HDCVI 4K	200 m
Distancia de transmisión HDTVI 720p	250 m
Distancia de transmisión HDTVI 1080p	250 m
Distancia de transmisión HDTVI 4K	130 m
Distancia de transmisión AHD 720p	320 m
Distancia de transmisión AHD 1080p	250 m
Distancia de transmisión analógicas	400 m
Forma de conexión	BNC
Impedancia de entrada	100 Ohm
Impedancia de salida	100 Ohm
Formatos compatibles	HDCVI / HDTVI / AHD / Analogic
Resolución	1 Mpx / 2 Mpx / 3 Mpx / 4 Mpx / 5 Mpx / 8 Mpx
Transmission distance HDCVI 4Mpx	200 m
HDTVI 4Mpx transmission distance	180 m
Transmission distance AHD 4Mpx	200 m
Distancia de transmisión AHD 4K	150 m

VIDEO (BALUN)

Número de canales	1
Entrada	RJ45
Salida	BNC Macho y DC Hermbra

AMBIENT

Operating temperature	-10 °C ~ 55 °C
Maximum humidity	95%

PROTECTION

ESD Conector cable coaxial	2KV
ESD Conector cable UTP	2KV

MATERIAL AND DIMENSIONS

Dimensions	61.5 x 33.5 x 20.5 mm
Material	ABS plastic
Net weight	40 g
Weight with packaging	100 g

GENERAL INFORMATION

Type	Passive
Subtipo	Emitter / receiver
Units	2

POWER CONSUMPTION

Power mode	DC
Voltage	12V ~ 15V

CHARACTERISTICS (BALUNS)

Categoría del cable	UTP category 5E / 6
Type	Video / Power supply

