



2 wire of surface video intercom DS-KV8103Y-IMPE2

INPUTS/OUTPUTS

Alarm input	2
Door sensor	2
Exit button	2
Blocking entry	2
Alarm output	1 (12V, 500mA)

AMBIENT

Operating temperature	-40 °C ~ 60 °C
Degree of protection	IP65
Use	Outdoor
Maximum humidity	95%

SYSTEM (RECORDERS)

Processor	Embedded MCU Processor
Operating system	Embedded LINUX
RAM	256 MB
ROM	32 MB

AUDIO (VIDEO INTERCOM)

Sound input	Omni-directional microphone
Sound output	Built-in speaker
Audio compression	G.711A / G.711U

CAPACITY

Events	200
Extensiones interiores vinculadas	1

OPENING

Call elements	Simple button
---------------	---------------

MATERIAL AND DIMENSIONS

Installation	Surface
Dimensions	169 x 110 x 31 mm
Material	Stainless steel
Net weight	545 g

CAMERA

Resolution	2 Mpx
Horizontal viewing angle	140°
Night vision	Yes, up to 3 m
Video compression	H.264

POWER CONSUMPTION

Power mode	Powered via indoor station
Consumption (w)	10W

GENERAL CHARACTERISTICS (VIDEO INTERCOM)

Tamper	Sí
Led indicator	Sí, 3

GENERAL INFORMATION

Technology	2 Wire
------------	--------

NETWORK CHARACTERISTICS (INTERCOM MONITORS)

Network protocol	TCP / IP / SIP 2.0 / RSTP
------------------	---------------------------

