



10 ports cloud switch with 8 PoE ports

DS-3T1310P-SI/HS

GESTIÓN REMOTA

P2P	Yes
Software	Hik Pro Connect / IVSM4200
Reiniciar switch	Yes
Reinicio de puerto PoE	Yes
Activación de modo extendido	Sí, de forma independiente por puerto
Modificación de la velocidad del puerto	Yes
Consumo de potencia real	Sí, total y por puerto
Histórico de pico máximo de consumo	Yes (up to 7 days)
Información de tráfico a tiempo real	Sí, por puerto
Información del dispositivo conectado	Sí para equipos Hikvision (IP, modelo y SN)
Diagrama de topología automático	Sí, para dispositivos Hikvision conectados

CHARACTERISTICS (SWITCH)

Data rate supported	9.2 Gbps
Packet redirection speed	6.84 Mpps
VLAN	Yes (max 4094 VLAN)
Maximum transmission distance	300 m
Buffer Memory	4 Mb
PoE Watchdog	Yes
QoS	Yes
Industrial	Yes

MATERIAL AND DIMENSIONS

Installation	DIN rail / desktop
Dimensions	197 x 114.2 x 42.2 mm
Material	Metal
Net weight	590 g
Weight with packaging	1380 g

NET STANDARD

IEEE802.3af	Sí
IEEE802.3at	Sí

POWER CONSUMPTION

Power mode	DC
Voltage	48V
Consumption (w)	120W
Standby consumption	5W
Maximum consumption per port (PoE)	30W
Total maximum consumption (PoE)	110W

ETHERNET PORTS

POE ports	8
Puertos Uplink	1
Fiber port	1 x 1000
POE Ports Speed	10 / 100
Uplink ports speed	10/100/1000
Number of Ethernet ports	10

AMBIENT

Operating temperature	-30 °C ~ 65 °C
Use	Indoor
Maximum humidity	95%
Lightning protection	6KV

SYSTEM (SWITCH)

MAC address table	16K
-------------------	-----

