



Bullet ip camera of 5 megapixels and fix lens

IPC-HFW3549T1-AS-PV-S5

VIDEO (CAMERAS)

Video Resolution	5 Megapixels
BLC	Yes
HLC	Yes
3D-NR	Yes
AGC	Yes
AWB	Yes
WDR	WDR (120 dB)
Images per second	20fps
Video output	RJ45
Day / night mode	Colour
Privacy mask	Up to 4 zones
Anti fog system	Yes
Type of Codex	CBR / VBR / ABR
Bit rate	3Kbps ~ 16384Kbps
Compression	AI H.265 / AI H.264 / H.265 / H.264
Main stream	5Mpx (1 ~ 20fps)
Sub stream	704 × 576
Sub stream 2	1080P (1 ~ 25fps)
Watermark	Yes
Mirror	On / Off
SSA	Si
AI SSA	Yes

NIGHT VISION

Night vision distance	30 m
Type of night vision	Dual light (IR+Luz blanca)
Number of LEDs	2
IR ON/Off	Automatic / Manual
Starlight	Yes
Full Color	Yes
White light	2
White light distance	30 m
Smart Dual Illumination	Yes

IMAGE

VIDEO ANALYSIS

Detection type	Advanced detection (person/vehicle/pet classification)
AcuPick	Yes
Change of scene	Yes
Crossing line	Yes
Intrusion	Yes
Motion detection	Yes (4 areas)
Audio detection	Yes
Video Tamper	Si
Classification Human / vehicle	Yes
SMD 4.0	Yes

NETWORK FEATURES

IP connection	1 RJ45 (10M / 100M)
ONVIF	Yes, type S , G and T
Maximum number of users	20 users
Web browser	Explorer / Chrome / Firefox
Management software	Smart PSS Lite / DSS / DMSS
Mobile devices	Android / IOS (Apple)
Network disconnection	Yes
Conflict of IP addresses	Yes
Cybersecurity	Yes

POWER CONSUMPTION

Power mode	DC
Voltage	12V
Consumption (w)	8.3W
Amperage	700mA
PoE power	Yes
Type PoE	PoE 802.3af

LENS

Lens Type	Fix
Focal distance	2.8 mm
Maximum diaphragm opening	F/1.0

technical datasheet

Sensor	CMOS ®
Sensor resolution	2960 x 1668
Sensor Size	1/2.7"
Electronic shutter speed	1/3 ~ 1/100000s
Minimum lighting	Color: 0.003Lux / B/W: 0.0003Lux
Ratio S / N	More than 56dB

MATERIAL AND DIMENSIONS

Dimensions	288.4 x 94.4 x 84.7 mm
Material	Metal and plastic
Net weight	1000 g
Weight with packaging	1300 g
Color	White

AUDIO(CAMERAS)

Built in microphone	Yes
Audio input	1 Input
Built in speaker	Yes
Audio compression	G.711A / G.711U / G.723 / G.726 / PCM
Audio output	1

GENERAL INFORMATION

Serie	Active Deterrence
Technology	IP
Type of camera	Bullet

SYSTEM (CAMERAS)

Ram memory	1024 MB
ROM memory	256 MB

AXES

Motion	3-Axis
--------	--------

Angle of View	97°
---------------	-----

Minimum focus distance	1500mm
------------------------	--------

AMBIENT

Operating temperature	-40 °C ~ 60 °C
Degree of protection	IP67
Use	Indoor-outdoor
Maximum humidity	95%

DISTANCE DORI

Detect	66 m
Observe	26 m
Recognize	13 m
Identify	7 m

STORAGE

MicroSD-Card	Hasta 512Gb
Storage Systems	NAS / FTP / SFTP / Micro SD
Storage anomaly	Yes

TIOC

Siren	Yes
Light	blue/ red Light

INPUTS/OUTPUTS (CAMERAS)

Alarm	1 Input / 1 Output
-------	--------------------