technical datasheet





Ip recorder of 128 channel and 32 mpx resolution

NVR608H-128-XI

Maximum		Installation Desk / Rack Dimensions 440 x 455 x 95 mm		
recording	32 Mpx			
resolution	1200146			
Input bandwidth	1280Mbps	Material Metal		
Video compression	H.265 / H.264	Net weight 6900 g		
Channels that support the		Weight with packaging 9000 g		
maximum	2	Chassis	2U	
recording resolution		VIDEO OUTPUT		
Recording mode	General / motion detection / intelligent / alarm	HDMI Output Number	4	
Audio compression	G.711A / G.711U / G.726 / PCM	Number of VGA		
3	2Mpx / 24Mpx / 16Mpx / 12Mpx /	outputs		
Resolutions 44	(/ 6Mpx / 5Mpx / 4Mpx / 3Mpx / 1080p / 1.3Mpx / 720p / D1 / CIF	Resolution HDMI	HDMI 1 / 2: 4K / HDMI 3: 8K / HDMI 4: 1080P	
Output bandwidth	1024Mbps	VGA resolution	1080P	
NETWORK FEATURES		Similar video signals F	HDMI and VGA (configurable)	
Number of ports RJ45	2	Independent video Fignals	HDMI and VGA (configurable)	
Speed RJ45	10 / 100 / 1000 / 2500 Mbps	METADATA		
Mobile devices	Android / IOS (Apple)	Face Gender / 8	age / glasses / beard / mask / expression	
ONVIF	Yes	Vehícle Number plate / number plate colour / vehícle model / vehícle logo / vehícle decorations / call sign / seat belts Human Style of clothing / color of clothing / hat /		
Remote Web B	rowser (ActiveX) / Smartphone App / Smart PSS Software			
Software	SmartPSS	body	bag / umbrella	
Арр	iDMSS / gDMSS	• •	or / helmet / people in vehicle	
INPUTS/OUTPUTS		vehicle		
Alarm input	16	POWER CONSUMPTION		
USB 2.0	2	Power mode AC		
USB 3.0	2	Voltage	100V ~ 240V	
RS232		Consumption (w)	18W	
RS485	<u>.</u> 1			
	8	REPRODUCTION AND CO Simultaneous cameras in		
Alarm output	8	reproduction	64	
STORAGE		Backup mode	USB / Network device /	
Number of supported h	nard drives 8	Synchronized playback	eSATA device	
Maximum hard disk siz	e (Unit) 20 TB	зунстногиzей ріаураск	16	
Type HDD	3,5 SATA"	FACE RECOGNITION		

technical datasheet

16 (video stream) / 32 (image		Sí	eSata
stream) faces processed per second	Number of faces	0/1/5/6/10	Raid
8 channels video face	Number of		AMBIENT
recognition / 32 channels photo face recognition	channels with facial recognition	-10 °C ~ 55 °C	Operating temperature
Up to 40 databases with 300,000 faces in total	Database	Indoor	Use
	managment	93%	Maximum humidity
	AUDIO	STEM	INTELLIGENT VIDEO S
Audio Inputs 1		Yes, 8 channels, up to 12	INTELLIGENT VIDEO 3
2	Audio Outputs	frames / sec.	Face detection
CTION	PERIMETER PROTEC	Yes, 32 channels (human/vehicle classification)	SMD PLUS
32 channels / 10 IVS rules for each channel	Channels number with analytics	Yes	Acupick (intelligent object search)
Human secondary recognition /	ariarytics	N	GENERAL INFORMATION
vehicle for line crossing and intrusion	Type of identification	Serie 6	Serie
		IP	Technology

Industrial grade integrated

processor

128

Embedded LINUX

SYSTEM (RECORDERS)

Processor

Operating

IP Channels

system

VIDEO

