

**HIKVISION**  
HiWatch Series



## Minidome ip camera of 4 megapixels and fix lens

**HWI-T240HA-LUC**

### VIDEO (CAMERAS)

Video Resolution	<b>4 Megapixels</b>
BLC	<b>Yes</b>
HLC	<b>Yes</b>
3D-NR	<b>Yes</b>
AGC	<b>Yes</b>
AWB	<b>Yes</b>
WDR	<b>DWDR</b>
Images per second	<b>20fps</b>
Video output	<b>RJ45</b>
Day / night mode	<b>Automatic / Manual</b>
Privacy mask	<b>Yes</b>
Type of Codex	<b>CBR / VBR</b>
Bit rate	<b>32Kbps ~ 8Mbps</b>
Compression	<b>H.265+ / H.265 / H.264</b>
Main stream	<b>4Mpx (1 ~ 20fps) / 1080P / 720P (1 ~ 25fps)</b>
Sub stream	<b>720P / 640 x 480 / 640 x 360 (1 ~ 25fps)</b>
Watermark	<b>Yes</b>
Anti flap	<b>Yes</b>
Mirror	<b>On / Off</b>

### NETWORK FEATURES

IP connection	<b>1 RJ45 (10M / 100M)</b>
ONVIF	<b>Yes, S and T type</b>
Maximum number of users	<b>Up to 32 users</b>
Password protection	<b>Yes</b>
Web browser	<b>Explorer / Chrome / Firefox</b>
Management software	<b>iVMS-4200 / HiLookVision</b>
Mobile devices	<b>Android / IOS (Apple)</b>
Live view	<b>Up to 6 channels</b>

### POWER CONSUMPTION

Power mode	<b>DC</b>
Voltage	<b>12V</b>

### NIGHT VISION

Night vision distance	<b>20 m</b>
Type of night vision	<b>Dual light (IR+Luz blanca)</b>
Number of LEDs	<b>2</b>
IR ON/Off	<b>Yes</b>
White light	<b>Sí</b>
White light distance	<b>20 m</b>
Wavelength	<b>850 nm</b>
Smart Hybrid Light	<b>Yes (switches from IR to colour with human detection)</b>

### IMAGE

Sensor	<b>CMOS ®</b>
Sensor resolution	<b>2560 x 1440</b>
Sensor Size	<b>1/2.8'</b>
Electronic shutter speed	<b>1/3 ~ 1/100000s</b>
Minimum lighting	<b>0.01Lux</b>
Ratio S / N	<b>Más de 52dB</b>

### LENS

Lens Type	<b>Fix</b>
Focal distance	<b>2.8 mm</b>
Maximum diaphragm opening	<b>F/2.2</b>
Angle of View	<b>104°</b>
Minimum focus distance	<b>900mm</b>
Filtro IR	<b>Sí</b>

### AUDIO(CAMERAS)

Built in microphone	<b>Yes</b>
Audio compression	<b>G.711U / AAC-LC</b>
Noise filter	<b>SI</b>
Sampling frequency	<b>8kHz / 16kHz</b>
Bit rate	<b>64 Kbps (G.711) / 16 ~ 64 Kbps (AAC-LC)</b>

### MATERIAL AND DIMENSIONS

# technical datasheet

Consumption (w)	<b>5W</b>
Amperage	<b>420mA</b>
PoE power	<b>Yes</b>
Type PoE	<b>PoE 802.3af</b>

## AMBIENT

Operating temperature	<b>-30 °C ~ 45 °C</b>
Degree of protection	<b>IP67</b>
Use	<b>Indoor-outdoor</b>
Maximum humidity	<b>95%</b>

## DISTANCE DORI

Detect	<b>53 m</b>
Observe	<b>21 m</b>
Recognize	<b>10 m</b>
Identify	<b>5 m</b>

## VIDEO ANALYSIS

Detection type	<b>Advanced detection (human classification)</b>
Motion detection	<b>Yes</b>

Dimensions	<b>102.7 x 110 (Ø) mm</b>
Material	<b>Metal and plastic</b>
Net weight	<b>350 g</b>
Weight with packaging	<b>590 g</b>

## GENERAL INFORMATION

Serie	<b>HiWatch</b>
Technology	<b>IP</b>
Type of camera	<b>Minidome</b>

## AXES

Motion	<b>3-Axis</b>
--------	---------------

