



MOVOK

Minidome ip camera of 5 megapixels and fix lens

VK-IPC-T251-LI

VIDEO (CAMERAS)

Video Resolution	5 Megapixels
BLC	Yes
HLC	Yes
3D-NR	Yes
AGC	Yes
AWB	Yes
WDR	DWDR
Images per second	25fps
Video output	RJ45
Day / night mode	Colour
Privacy mask	Up to 4 zones
Type of Codex	CBR / VBR
Bit rate	3Kbps ~ 20480Kbps
Compression	H.265 / H.264
Main stream	5Mpx (1 ~ 25fps)
Sub stream	D1 (1 ~ 25fps)
Sub stream 2	720P (1 ~ 25fps)
Mirror	On / Off

POWER CONSUMPTION

Power mode	DC
Voltage	12V
Consumption (w)	3W
Amperage	250mA
PoE power	Yes
Type PoE	PoE 802.3af

NETWORK FEATURES

IP connection	1 RJ45 (10M / 100M)
ONVIF	Yes, G type
Web browser	Explorer
Management software	MOVOK (CMS)
Network disconnection	Yes
Conflict of IP addresses	Yes

MATERIAL AND DIMENSIONS

IMAGE

Sensor	CMOS ®
Sensor resolution	2880 x 1620
Sensor Size	1/2.7'
Electronic shutter speed	1/3 ~ 1/100000s
Minimum lighting	0.006Lux
Ratio S / N	More than 56dB

NIGHT VISION

Night vision distance	30 m
Type of night vision	Dual light (IR+Luz blanca)
IR ON/Off	Automatic / Manual
White light	Sí
White light distance	30 m
Smart Dual Illumination	Yes (switches from IR to colour with human detection)

VIDEO ANALYSIS

Detection type	Analytics with human/vehicle/non-motorized vehicle classification in line/area crossing
Crossing line	Yes
Intrusion	Yes
Motion detection	Yes (4 areas)
Classification Human / vehicle	Yes
SMD	Yes

AMBIENT

Operating temperature	-30 °C ~ 60 °C
Degree of protection	IP67
Use	Indoor-outdoor
Maximum humidity	95%

LENS

Lens Type	Fix
Focal distance	2.8 mm
Maximum diaphragm opening	F/1.6

technical datasheet

Dimensions	97 x 110 (Ø) mm
Material	Metal and plastic
Net weight	350 g
Weight with packaging	480 g
Color	White

DISTANCE DORI

Detect	62 m
Observe	25 m
Recognize	12 m
Identify	6 m

AXES

Motion	3-Axis
--------	---------------

Angle of View	107°
---------------	-------------

GENERAL INFORMATION

Serie	Serie 2
Technology	IP
Type of camera	Minidome

STORAGE

Storage Systems	FTP
-----------------	------------

