



IP / 2-wire Video Intercom with camera

VTO4202FB-P-S3

POWER CONSUMPTION

Power mode	DC
Voltage	48V
Amperage	1000mA
PoE power	Yes
Type PoE	PoE 802.3af / PoE+ 802.3at
Standby consumption	≤4W
Consumption On	5W
Power output	1 x 12V DC / 600mA

CAMERA

Resolution	2 Mpx
Sensor	CMOS
Sensor size	1/2.9"
Horizontal viewing angle	169°
Diagonal angle of view	177°
Day / Night	IR
Video compression	H.265

INPUTS/OUTPUTS

RS485	1
Door sensor	1
Exit button	1
Blocking entry	1
Alarm output	1

GENERAL INFORMATION

Technology	2 Wires / IP
Type	IP / 2-wire Video Intercom with camera

GENERAL CHARACTERISTICS (VIDEO INTERCOM)

Memory slot	SD up to 256Gb
Message recording if no response	Yes (SD card required)

CAPACITY

Cards	3000
-------	-------------

AMBIENT

Operating temperature	-30 °C ~ 60 °C
Degree of protection	IP65
Anti vandal	IK07
Use	Indoor-outdoor
Maximum humidity	90%

MATERIAL AND DIMENSIONS

Installation	Surface / embed
Dimensions	100 x 100 x 49.3 mm
Net weight	300 g
Weight with packaging	470 g
Color	Black

AUDIO (VIDEO INTERCOM)

Sound input	1
Sound output	Built-in speaker
Bidirectional audio	Si
Audio compression	G.711A/G.711U/PCM

SYSTEM (RECORDERS)

Processor	Embedded Processor
Operating system	Embedded LINUX

NETWORK CHARACTERISTICS (INTERCOM MONITORS)

Network protocol	SIP / P2P / IPv4 / UPnP / DNS / RTSP / RTP / TCP / UDP
ONVIF	Yes

